

LIGHTING RECOMMENDATIONS

1 .RECEIVING BAY	40+FC**
2. RAW MILK PROCESSING	60+FC**
3. PROCESSING ROOM	60+FC**
4. BOTTLING ROOM	60+ FC**
5. BOTTLE WASHING ROOM	40+FC**
6. STORAGE ROOM	35+FC**

THE ABOVE ARE LIGHT LEVEL **RECOMMENDATIONS** FOR VARIOUS DAIRY PROCESSING SPACES

FC= FOOT CANDLES

NOTE: A MINIMUM OF 20 FC FOR ALL PROCESSING AREAS AND 5 FC FOR STORAGE AREAS WILL BE REQUIRED BY THE PMO.* LIGHTING MAY BE NATURAL, ARTIFICIAL OR A COMBINATION OF BOTH.

PMO

* ITEM 4p. LIGHTING AND VENTILATION

1. Adequate light sources are provided (natural, artificial or a combination of both) which furnish at least twenty (20) foot-candles (220 lux) of light in all working areas. This shall apply to all rooms where milk or milk products are handled, processed, packaged, or stored; or where containers, utensils and/or equipment are washed. Dry storage and cold storage rooms shall be provided with at least five (5) foot-candles (55 lux) of light.

** This document in no way represents the final authority on the subject matter contained within and is Conococheague Stainless LLC recommendation only. The customer should verify the requirements with their Milk Authority and with any pertaining local or state codes or requirements. Conococheague Stainless LLC is not liable for any insufficient conditions resulting from a recommendation. All recommendations are based on Conococheague Stainless LLC experience and other information obtained from additional sources