

Automatic Two-Valve Filler/Capper (CS-BF2A)

FILLER

Overall Dimensions (LWH)	57" x 48" x 88"
Table Dimensions (LWH)	40" x 32" x 36"
Interface	Touchscreen
Bottles per Minute	Up to 10
Fill Speeds	6 Customizable Presets
Power Requirements	15FLA 120VAC 1Ø
Air Requirements	80 psi, 5 cfm
Stainless Type	304
Stainless Finish	#4 and bead-blasted

BOWL

Capacity	8.5 gal.
Inside Diameter	14"
Depth	16"
Maximum Fill Depth	13"
Stainless Type	304
Stainless Finish	#4

COMPATIBLE BOTTLES

Plastic	Gallon, Half Gallon, Quart, Tall Quart, Pint, Square Pint, Round Pint
Glass	Half Gallon, Quart, Pint, Squat Pint

COMPATIBLE CAPS

Plastic	SC2 (Snap Cap), DBJ (Screw Cap)
Glass	Stanpac (Snap Cap)

WEIGHT

600 lb.

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty (see warranty document)

OPTIONS

Conveyor
Infeed and outfeed tables
Float level control for automatic bowl filling



Easily change starwheels for different bottle sizes



All specifications are subject to change without notice.