

Crate Washer (CS-CW)

SPECIFICATIONS

| | |
|-----------------------------|------------------|
| Exterior Dimensions (LWH) | 145" x 38" x 49" |
| Wash Tank Dimensions (LWH) | 48" x 30" x 29" |
| Rinse Tank Dimensions (LWH) | 30" x 30" x 29" |
| Rail Height | 30" |
| Max Fill Depth | 6" |
| Wash Loops | 2 |
| Rinse Loops | 1 |
| Filtration | Included |
| Plumbing | Included |
| Stainless Type | 304 |
| Stainless Finish | #4 |
| Stainless Thickness | 12 Ga. |

WASH TANK HEATING JACKET

| | |
|-----------------------|---------------|
| Type | Dimple Jacket |
| Minimum Heat Required | 75,000 BTU/h |
| Water Thickness | 0.375" |
| Max Pressure | 40 PSI |
| Port Size | 1.5" |

PUMPS

| | |
|---------------|-------------|
| Type | Centrifugal |
| Wash Pump HP | 3 |
| Rinse Pump HP | 0.75 |
| Phase | 3Ø |
| Voltage | 230/460 VAC |
| FLA | 11/6 |

WEIGHT

770 lb.

OPTIONS

Crate conveyer
Electrical control
Stainless steel plumbing

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty
(see warranty document)



All specifications are subject to change without notice.