

## 10,000 lb. Finishing Table (CS-FT10)

### VAT

Rated Vat Capacity <sup>1</sup>	10,000 lb.
Overall Dimensions (LWH)	219" x 60" x 83"
Vat Inner Dimensions (LW)	198" x 54"
Vat Outer Dimensions (LW)	204" x 60"
Floor to Top of Vat Wall	36"
Total Depth	15"
Inner Vat Thickness	10 Ga.
Exterior Vat Thickness	12 Ga.
Material Type	304 Stainless Steel
Surface Finish	#4

### AGITATOR

Type	Travelling forks
Agitator Motor	2HP 3Ø
Agitator Gearbox Ratio	60:1
Agitator Speed	29 RPM
Carrier Motor	0.75HP 3Ø

### POWER REQUIREMENTS

Voltage	230/460 VAC
FLA	10/5

### INSULATION

Side & Bottom	Closed cell polyurethane R12
---------------	---------------------------------

### HEATING REQUIREMENTS

Minimum Heating Required	1,000,000 BTUh
--------------------------	----------------

### HEATING JACKET

Type	Dimple Jacket
Water Thickness	0.375"
Maximum Pressure	50 PSI
Inlet and Outlet Port Size	2"
Flow Rate	40 GPM minimum

### OUTLET VALVE

2.5" SS minidisc valve

### WEIGHT

2670 lb.

### WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty  
(see warranty document)

<sup>1</sup>Capacity based on 10,000 lb. cheese vat



All specifications are subject to change without notice.