

5,000 lb. Finishing Table (CS-FT05)

VAT

Rated Vat Capacity ¹	5,000 lb.
Overall Dimensions (LWH)	159" x 54" x 83"
Vat Inner Dimensions (LW)	144" x 48"
Vat Outer Dimensions (LW)	150" x 54"
Floor to Top of Vat Wall	36"
Total Depth	15"
Inner Vat Thickness	10 Ga.
Exterior Vat Thickness	12 Ga.
Material Type	304 Stainless Steel
Surface Finish	#4

AGITATOR

Type	Travelling forks
Agitator Motor	1HP 3Ø
Agitator Gearbox Ratio	60:1
Agitator Speed	29 RPM
Carrier Motor	0.5HP 3Ø

POWER REQUIREMENTS

Voltage	230/460 VAC
FLA	5.0/2.5

INSULATION

Side & Bottom	Closed cell polyurethane R12
---------------	---------------------------------

HEATING REQUIREMENTS

Minimum Heating Required	500,000 BTUh
--------------------------	--------------

HEATING JACKET

Type	Dimple Jacket
Water Thickness	0.375"
Maximum Pressure	50 PSI
Inlet and Outlet Port Size	2"
Flow Rate	40 GPM minimum

OUTLET VALVE

2.5" SS minidisc valve

WEIGHT

1890 lb.

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty
(see warranty document)

¹Capacity based on 5,000 lb. cheese vat



All specifications are subject to change without notice.