

## 1000 Gal. Vat Pasteurizer (CS-VP10)

### VAT

Rated Vat Capacity	1,000 gal.
Inside Diameter	72"
Outside Diameter	76"
Depth	60"
Overall Height	100"
Lid Type	Dome
Inner Vat Thickness	12 Ga.
Exterior Vat Thickness	14 Ga.
Stainless Type	304
Stainless Finish	#4

### AGITATOR

Type	Full Sweep
Motor HP	1.5
Motor Phase	3Ø
Motor Voltage	230/460 VAC
Motor FLA	4.2/2.1
Gearbox Ratio	60:1
Agitator Speed	28 RPM

### HEATING REQUIREMENTS

Minimum Heating Required	1,000,000 BTUh
--------------------------	----------------

### HEATING JACKET

Type	2-zone dimple jacket (bottom, side zones)
Water Thickness	0.375"
Maximum Pressure	70 PSI
Inlet and Outlet Port Size	Dual 2"
Flow Rate	80 GPM minimum
Capacity	10 gal.

### INSULATION

Side & Bottom	1.5" rigid fiberglass
---------------	-----------------------

### OUTLET

Mounting flange to fit 2" D10F leak detect valve

### WEIGHT

2,150 lb.

### WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty  
(see warranty document)

### OPTIONS

Air space heating  
Anderson AJ300 temperature recorder package  
CIP spray ball package  
Variable speed drive / phase converter  
Sidewall agitation  
2" D10F leak detect valve  
Baffle  
Ladder  
Dip stick



All specifications are subject to change without notice.