

200 Gal. Vat Pasteurizer (CS-VP02)

VAT

Rated Vat Capacity	200 gal.
Inside Diameter	45.5"
Outside Diameter	50"
Depth	33"
Overall Height	66"
Lid Type	Butterfly Lids
Inner Vat Thickness	12 Ga.
Exterior Vat Thickness	14 Ga.
Stainless Type	304
Stainless Finish	#4

AGITATOR

Type	Sweep
Motor HP	0.5
Motor Phase	3Ø
Motor Voltage	230/460 VAC
Motor FLA	2.2/1.1
Gearbox Ratio	60:1
Agitator Speed	29.2 RPM

HEATING REQUIREMENTS

Minimum Heating Required	200,000 BTU/h
--------------------------	---------------

HEATING JACKET

Type	2-zone dimple jacket (bottom, side zones)
Water Thickness	0.375"
Maximum Pressure	70 PSI
Inlet and Outlet Port Size	Dual 2"
Flow Rate	40 GPM minimum
Capacity	4.5 gal.

INSULATION

Side & Bottom	1.5" rigid fiberglass
---------------	-----------------------

OUTLET

Mounting flange to fit 2" D10F leak detect valve

WEIGHT

810 lb.

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty
(see warranty document)

OPTIONS

Air space heating
Anderson AJ300 temperature recorder package
CIP spray ball package
Variable speed drive / phase converter
Dome top
Removable lids with swing-away agitation*
Full sweep agitation
Sidewall agitation
2" D10F leak detect valve
Baffle
Dip stick

*This option changes the vat dimensions



All specifications are subject to change without notice.