

50 Gal. Vat Pasteurizer (CS-VP00)

VAT

Rated Vat Capacity	50 gal.
Inside Diameter	34"
Outside Diameter	38"
Depth	20"
Overall Height	46"
Lid Style	Removable Lid
Inner Vat Thickness	12 Ga.
Exterior Vat Thickness	14 Ga.
Stainless Type	304
Stainless Finish	#4

AGITATOR

Type	Sweep
Motor HP	0.125
Motor Phase	3Ø
Motor Voltage	230/460 VAC
Motor FLA	1.8/0.9
Gearbox Ratio	59:1
Agitator Speed	29.7 RPM

HEATING REQUIREMENTS

Minimum Heating Required	75,000 BTUh
--------------------------	-------------

HEATING JACKET

Type	Single-zone bottom dimple jacket
Water Thickness	0.375"
Maximum Pressure	70 PSI
Inlet and Outlet Port Size	1"
Flow Rate	20 GPM minimum
Capacity	3 gal.

INSULATION

Side & Bottom	1.5" rigid fiberglass
---------------	-----------------------

OUTLET

Mounting flange to fit 2" D10F leak detect valve

WEIGHT

400 lb.

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty
(see warranty document)

OPTIONS

Air space heating
Anderson AJ300 temperature recorder package
Variable speed drive / phase converter
2" D10F leak detect valve
Dip stick



All specifications are subject to change without notice.