

Yogurt Cup Filler (CS-CF)

FEATURES

- Handles the entire filling, sealing, and (optional) overlid process
- Modular design makes it quick and easy to change between cup sizes
- User-friendly touch screen interface
- Cup counter for tracking the amount of product packaged
- Modular cup, foil, and lid stations operated by air pressure
- Turn table with interchangeable cup inserts

OPTIONS

- Cup drop station
- Overlid station
- Cup eject station
- Funnel level sensor for level control and empty warnings
- Foil sensor for detecting missed foil seals
- Cup sensor for detecting missing cups
- Fruit pump station for fruit-on-the-bottom yogurt
- 316 stainless steel for product contact components
- All-stainless turn table

SPECS

Overall Dimensions (LWH)	56" x 48" x 84"
Frame Thickness	10 Ga.
Stainless Type	304
Stainless Finish	#4, bead-blasted
Air Requirements	10 cfm @ 120 psi
Power Requirements	15FLA 240VAC 1Ø
Dosing Pump	Stepper-powered piston
Max Fill Size	32 oz.
Speed	15 – 25 cups/min.

WEIGHT

700 lb.

WARRANTY

Conococheague Stainless LLC 1-Year Limited Warranty
(see warranty document)



Yogurt cup



Foil seal



Overlid
(optional feature)



All specifications are subject to change without notice.